



# ULTRA-PERFORMANCE CLEAR FDA GREASE

## CLEAR SYNTHETIC FOOD SERVICE GREASE

### BEYOND SYNTHETIC®

Ultra-Performance Clear FDA Grease is a colorless, non-staining, nondrying, biodegradable, aluminum complex H-1 grease. Is NSF certified for use in federally inspected meat and poultry plants. Ultra-Performance Clear FDA Grease meets or exceeds the FDA CFR Title 21 Section 178.3570 purity regulation and is specifically designed for use in the food processing industry where it may have incidental contact with food.

Ultra-Performance Clear FDA Grease contains a bacteriostatic agent to retard bacterial and fungus growth. It is extremely water resistant even after frequent wash downs. Polymer additives provide superior adhesive/cohesive strength to lower friction and protect against high shock loads.

Ultra-Performance Clear FDA Grease is an undyed product.

### PERFORMANCE ADVANTAGES

#### Aluminum Complex Grease Base

Ultra-Performance Clear FDA Grease has an adhesive, non-drip base that provides superior shear stability, water resistance and high temperature performance.

#### Multi-Temperature Service

Ultra-Performance Clear FDA Grease's synthetic molecules combine both low temperature pumpability and high temperature stability. It is suitable for centralized pressure systems.

#### Bacteriostatic Agent

Ultra-Performance Clear FDA Grease retards bacterial and fungus growth.

#### Increases Food Machinery Life

Ultra-Performance Clear FDA Grease contains synthetic ingredients and anti-wear additives.

|                           |        | NLGI Grade       |
|---------------------------|--------|------------------|
| Typical Properties*       | Method | 1.5              |
| Thickener Type            |        | Aluminum Complex |
| Viscosity                 | D445   |                  |
| cSt @ 40°C                |        | 126              |
| cSt @ 100°C               |        | 15               |
| Rust Test                 | D665   | PASS             |
| Drop Point, °F/°C         | D2265  | 500/260          |
| Cone Penetration Test, mm | D217   | 300              |
| Copper Corrosion Test     | D4048  | 1A               |

*\*Properties are typical and may vary.*